



100mm BALL VALVE FLANGED

316 Stainless Steel

A.D.R. Certified

EUROPEAN STANDARD EN14432:2014

DATA SHEET and MATERIAL CERTIFICATE

for

SERIAL NUMBER : AMF-BA-100-MAN-ADR-316

SN: #####

PART	MATERIAL
MAIN BODY	STAINLESS STEEL G316
WORKING PARTS	STAINLESS STEEL G316
SHAFT BUSH, SPACER	PTFE
O-RINGS	VITON, VITON ENCAPSULATED
FASTENERS	STAINLESS STEEL

* - If applicable, copies of material certificates available on request

PRODUCTION TEST CERTIFICATE

for

SERIAL NUMBER : AMF-BA-100-MAN-ADR-316

ACCEPTANCE CRITERIA (unless otherwise specified)

"A" - BS EN 12266-1:2012 TABLE A.5 RATE "A" - NO VISUALLY DETECTABLE LEAKAGE

ITEM	TYPE OF TEST	CRITERIA	DURATION	RESULT	
1	SHELL STRENGTH	900kPa	"A"	60 seconds	PASSED
2	SHELL TIGHTNESS	520kPa	"A"	60 seconds	PASSED
3	SEAT TIGHTNESS	40 & 400 kPa	"A"	60 seconds	PASSED