



50mm FLANGED CAM DRY BREAK COUPLING with 3 WAY VALVE

316 Stainless Steel

BRITISH STANDARD EN13315:2002

DATA SHEET and MATERIAL CERTIFICATE

for

PRODUCT CODE: AMF-CAM-DB-FL-3WAY-50-316

SN: #####

PART	MATERIAL
MAIN BODY	G316 STAINLESS STEEL
SEALING DISC, SEALING DISC ROD, SPIDER	G316 STAINLESS STEEL
SEALS	PTFE & VITON ENCAPSULATED
3 WAY AIR VALVE	STAINLESS STEEL & ALUMINIUM
FASTENERS	STAINLESS STEEL

* - If applicable, copies of supplier material certificates available on request

PRODUCTION TEST REQUIREMENTS

Acceptance criteria: as per table A.3 (EN12266-1:2012)

"A" No visually detectable leaks for the duration of the test

TEST #	TEST TYPE	TEST FLUID	TEST DURATION Table A.2	TEST CRITERIA Table A.3.4	RESULT
1	Shell Tightness (P11)	Water	60 seconds	no visible leaks	PASSED
2	Operability (F20)	Air	n/a	open - close	PASSED

TESTING PRESSURE

TYPE TEST	TEST PRESSURE
Shell Tightness	500kPa