

PRODUCT FACT SHEET / FILLER HATCH 200mm ID

SPECIFICATIONS

PRODUCT CODE	AMF-FH-200-4.5-230-316
MATERIAL	STAINLESS STEEL 316
O-RING / SEALS	VITON A
DESIGN CODE	AMF
MAWP	200kPa
MAX. TEMP	+50 ° CELSIUS
MIN. TEMP	-20 ° CELSIUS



INSTALLATION, APPLICATION & MAINTENANCE

COMPATIBLE PRODUCTS

1. FUELS

- * Petrol
- * Diesel
- * Paraffin

2. INDUSTRIAL SOLVENTS

- * Alcohols
- * Benzene
- * Toluene

3. VARIOUS ACIDS

(Examples of compatible products, but not limited to. Contact AMF SALES for additional confirmations)

DESIGN AND APPLICATION

The 200mm Filler Hatch is designed and manufactured to be Welded into any existing manhole lid or tank barrel.

The AMF filler hatch is fitted with a single hinge and secured with one easy fastening eyebolt. The filler hatch can easily be opened to allow for fast top loading, and for inspection purposes.

The filler hatch is supplied with a versatile Viton seal as standard that is suited for transport of a wide variety of products.

MAINTENANCE

Filler hatches are largely maintenance free.

Depending on type and usage the filler hatch seal should be regularly inspected and is easily replaced when worn or damaged.

PRODUCTION TESTING REQUIREMENTS

TEST #	TEST TYPE	TEST FLUID	TEST DURATION	TEST PRESSURE	TEST CRITERIA
1	Seat Tightness	Water	10 Min	350kPa	No visible leaks

WARNING: Use only genuine AMF replacement parts. Substitute parts can impair the proper functioning of this product and void all warranties. Failure to properly maintain and regularly clean the complete valve, especially moving parts, may prevent the valve from operating correctly as per its design, and subject to liability disclaimer.