



Polypropylene Manhole Cover 50mm thick w/ 16 bolt holes @ 21mm 790BCD supplied with
2 x 50mm Camlock couplings & 1 x 80mm Camlock coupling with polypropylene dust caps
1 x 100mm Combined Vacuum/Pressure relief valve
1 x 150mm Table D Flange
1 x Viton Seal 840mm OD x 2mm

DATA SHEET and MATERIAL CERTIFICATE
PRODUCT CODE: AMF-MH-16B-50-50C-80C-100VP-TD6-PP
S/N: #####

PART	MATERIAL
MANHOLE COVER	POLYPROPYLENE
50mm & 80mm CAMLOCK COUPLING	POLYPROPYLENE
100mm COMBINED VACUUM/PRESSURE VENT	POLYPROPYLENE
TABLE D FLANGE	POLYPROPYLENE
DUST CAPS	POLYPROPYLENE
CLOSURE KITS	G316 STAINLESS STEEL & POLYPROPYLENE
SEAL	VITON

* - If applicable, copies of supplier material certificates available on request

PRODUCTION TEST REQUIREMENTS

Acceptance criteria: as per table A.5 (EN12266-1:2012)

"A" No visually detectable leaks for the duration of the test

TEST #	TEST TYPE	TEST FLUID	TEST DURATION Table A.4.	TEST CRITERIA Table A.5	RESULT
1	Seat Tightness (Test P12)	Water	60 seconds	No visible leaks	Pass

TESTING PRESSURE

TYPE TEST	TEST PRESSURE
Seat tightness	100kPa