

## PRODUCT FACT SHEET / HYPALON MANHOLE SEAL

### SPECIFICATIONS

PRODUCT CODE  
MATERIAL  
MAX. TEMP  
MIN. TEMP

AMF-MH-GA-500-Hypalon  
HYPALON  
+121 ° CELSIUS  
-54 ° CELSIUS



### INSTALLATION, APPLICATION & MAINTENANCE

#### COMPATIBLE PRODUCTS

1. WATER
2. SOLVENTS
3. SILICONE OILS & GREASE

#### 4. FUELS

- Petrol
- Diesel
- Paraffin

#### 5. VARIOUS ACIDS

(Examples of compatible products, but not limited to. Contact AMF SALES for additional confirmations)

#### DESIGN AND APPLICATION

The Hypalon manhole seal is designed to offer outstanding durability and flexibility, maintain their sealing performance over a wide range of operating conditions.

The Hypalon seal is a synthetic rubber that offers a unique combination of properties, making it suitable for a variety of sealing applications.

Key characteristics of Hypalon are:

- Chemical resistance
- Heat resistance
- Abrasion resistance
- Flame resistance
- Low moisture absorption
- High thermal stability

#### MAINTENANCE

The Hypalon seal offers a good operational life and is easily replaced when worn or damaged.

Regular inspection is advised to ensure all wear and tear items are in good working order.

**WARNING:** Use only genuine AMF replacement parts. Substitute parts can impair the proper functioning of this product and void all warranties. Failure to properly maintain and regularly clean the complete valve, especially moving parts, may prevent the valve from operating correctly as per its design, and subject to liability disclaimer.