

Allgemeine Maschinen Fabrik (Northwest) CC

20 Meul Street, George Industria, 6529 P.O. Box 1819, George, 6530 T: 0027 44 873 4649/56 sales@amf.co.za

# PRODUCT FACT SHEET / 6 LUG 4.5mm MANHOLE COVER FITTED WITH 110mm EMERGENCY AND 32mm COMBINED VACUUM/PRESSURE RELIEF VALVE

# **SPECIFICATIONS**

PRODUCT CODE
MATERIAL
O-RING / SEALS
APPROVAL CODES
MAWP
MAX. TEMP
MIN. TEMP

AMF-MHA-6-4.5-VE32-VE110-ADR-316 STAINLESS STEEL 316 HYPALON or VITON BS EN 13317 & 14025, ADR CERTIFIED 200kPa +50 ° CELSIUS -20 ° CELSIUS



# **INSTALLATION, APPLICATION & MAINTENANCE**

## **COMPATIBLE PRODUCTS**

#### 1. FUELS

- \* Petrol
- \* Diesel
- \* Paraffin

#### 2. INDUSTRIAL SOLVENTS

- \* Alcohols
- \* Benzene
- \* Toluene

(Examples of compatible products, but not limited to. Contact AMF SALES for additional confirmations)

## **DESIGN AND APPLICATION**

The 6 Lug 4.5mm Manhole Cover is designed and manufactured to comply with the European Standard EN BS 14025, SANS 1518 and the ADR, for the application of transportation of hazardous goods by road.

The AMF manhole cover is fitted with a single hinge and secured by six easy fastening eyebolts. Manhole covers can easily be opened to allow for top loading, internal tank cleaning and access to the compartment.

The manhole cover is supplied with Hypalon or Viton seals and is fitted with an 110mm emergency, and 32mm combined vacuum / pressure relief valve for the transport of hazardous goods with low flash point and to regulate atmospheric pressure change.

## MAINTENANCE

Manhole covers are largely maintenance free.

Depending on type and usage the manhole cover seal and swing kits should be regularly inspected and serviced and is easily replaced when worn or damaged.

## PRODUCTION TESTING REQUIREMENTS

| TEST # | TEST TYPE      | TEST FLUID | TEST DURATION | TEST PRESSURE | TEST CRITERIA    |
|--------|----------------|------------|---------------|---------------|------------------|
| 1      | Seat Tightness | Water      | 10 Minutes    | 300kPa        | No visible leaks |

**WARNING:** Use only genuine AMF replacement parts. Substitute parts can impair the proper functioning of this product and void all warranties. Failure to properly maintain and regularly clean the complete valve, especially moving parts, may prevent the valve from operating correctly as per its design, and subject to liability disclaimer.