



**MANHOLE COVER 6 LUG 4.5mm with 32mm combined vacuum/pressure relief valve
and 110mm emergency pressure relief valve apertures**

316 Stainless Steel

EUROPEAN STANDARD EN 14025, SANS 1518:2020 and ADR

DATA SHEET and MATERIAL CERTIFICATE

for

PRODUCT CODE: AMF-MH-6-4.5-VE32-VE110-ADR-316

SN: #####

PART	MATERIAL
RING, DISH, LUGS	STAINLESS STEEL
FLANGE, SOCKET & DUST CAP	STAINLESS STEEL
FILLER WIRE	STAINLESS STEEL
SWING KIT	STAINLESS STEEL

* - If applicable, copies of supplier material certificates available on request

PRODUCTION TEST REQUIREMENTS

Acceptance criteria: as per table A.5 (EN12266-1:2012)

"A" No visually detectable leaks for the duration of the test

TEST #	TEST TYPE	TEST FLUID	TEST DURATION Table A.4.	TEST CRITERIA Table A.5	RESULT
1	Seat Tightness (Test P12)	Water	60 seconds for 10 minutes	No visible leaks	PASS

TESTING PRESSURE

TYPE TEST	TEST PRESSURE
Seat Tightness	300kPa