

PRODUCT FACT SHEET / 62mm NON-RETURN VALVE

SPECIFICATIONS

PRODUCT CODE
MATERIAL
O-RING / SEALS
DESIGN CODE

AMF-NRV-62-TH-316
STAINLESS STEEL 316
PTFE ENCAPSULATED
AMF



INSTALLATION, APPLICATION & MAINTENANCE

COMPATIBLE PRODUCTS

1. FOOD GRADES

(Examples of compatible products, but not limited to. Contact AMF SALES for additional confirmations)

DESIGN AND APPLICATION

The design and primary function of the AMF 62mm non-return valve is to allow fluid to flow in one direction while preventing reverse flow.

With its hygienic design and durable robust G316 Stainless Steel construction makes the 62mm non-return valve particularly suitable for all process applications with higher hygienic requirements like in the transportation of food grade products.

The 62mm non-return valve excellent surface quality allows for an easy and efficient cleaning process through a CIP system.

The 62mm non-return valve is easily maintained and offers a good operational life.

MAINTENANCE

Care must be taken to avoid damaging the seal or the internal sealing area of the valve.

Clean regularly with appropriate cleaning agent to prevent product build up or damage to moving parts.

PRODUCTION TESTING REQUIREMENTS

TEST #	TEST TYPE	TEST FLUID	TEST DURATION	TEST PRESSURE	TEST CRITERIA
1	Seat Tightness	Water	5 Min	30kPa	No visible leaks

WARNING: Use only genuine AMF replacement parts. Substitute parts can impair the proper functioning of this product and void all warranties. Failure to properly maintain and regularly clean the complete valve, especially moving parts, may prevent the valve from operating correctly as per its design, and subject to liability disclaimer.