



OPTIC OVERFILL SENSOR HOUSING WITH QUICK RELEASE FLANGE

Flanged 130mm BCD

316 Stainless Steel

BRITISH STANDARD EN13922:2011

COMPATIBLE WITH DIXON FT100S OPTIC SENSOR

*** DIXON OPTIC SENSOR NOT SUPPLIED ***

DESIGNED FOR FLAMMABLE PETROLEUM PRODUCTS

DATA SHEET and MATERIAL CERTIFICATE

for

PRODUCT CODE: AMF-OFS-OPD-316

SN: ####

PART	MATERIAL
MAIN BODY	G316 STAINLESS STEEL
IMMERSION TUBE	G316 STAINLESS STEEL
SPRING	STAINLESS STEEL
SEALS	PTFE & VITON ENCAPSULATED
FASTENERS	STAINLESS STEEL
MAXIMUM WORKING TEMPERATURE	80 DEGREES

* - If applicable, copies of supplier material certificates available on request

PRODUCTION TEST REQUIREMENTS

Acceptance criteria: EN13922:2012

TEST #	TEST TYPE	TEST FLUID	TEST DURATION Table A.4.	TEST CRITERIA Table A.5	RESULT
1	Performance test	n/a	n/a	Table A.11 to A.15	PASS
2	EMC	n/a	n/a	EN 61000-6-4 and 61000-6-2	PASS
3	Production test	Diesel	n/a	annexure A: Table A.1	PASS