



A.D.R. COMPLIANT & CERTIFIED 32mm COMBINED VACUUM/PRESSURE

BREATHER VALVE WITH SPLASH GUARD

316 Stainless Steel

BRITISH STANDARD EN14595:2005

DATA SHEET and MATERIAL CERTIFICATE

for

PRODUCT CODE: AMF-RV-32VP-SG-ADR-316

S/N: ####

PART	MATERIAL
MAIN BODY	STAINLESS STEEL
BALL	STAINLESS STEEL
SPRING	STAINLESS STEEL
STRAINER	STAINLESS STEEL
MAXIMUM WORKING TEMPERATURE	200 DEGREES

* - If applicable, copies of supplier material certificates available on request

PRODUCTION TEST REQUIREMENTS

Acceptance criteria: as per table A.5 (EN12266-1:2012)

"A" No visually detectable leaks for the duration of the test

"B" DN32 x 0.01 cubic millimetres per second

TEST #	TEST TYPE	TEST FLUID	TEST DURATION Table A.4.	TEST CRITERIA Table A.5	RESULT
1	Seat Tightness (P12)	Water	60 seconds	No visible leaks	PASS
2	Overturn Seat Tightness	Water	60 seconds	1 drop/second	PASS

TESTING PRESSURE

TYPE TEST	TEST PRESSURE
Pressure (open)	7kPa
Vacuum (open)	3kPa