



36mm PRESSURE RELIEF SIDE OUTLET VALVE

316 Stainless Steel

A.D.R. Compliant

BRITISH STANDARD EN14595:2016

DATA SHEET and MATERIAL CERTIFICATE

for

PRODUCT CODE: AMF-RV-36PRE-TH-ADR-316

SN: #####

PART	MATERIAL
MAIN BODY	G316 STAINLESS STEEL
SEALS	VITON ENCAPSULATED
SPRING	STAINLESS STEEL
STRAINER	STAINLESS STEEL

* - If applicable, copies of supplier material certificates available on request

PRODUCTION TEST REQUIREMENTS

Acceptance criteria: as per table A.5 (EN12266-1:2012)

"A" No visually detectable leaks for the duration of the test

"B" DN32 x 0.01 cubic millimetres per second

TEST #	TEST TYPE	TEST FLUID	TEST DURATION Table A.4.	TEST CRITERIA Table A.5	RESULT
1	Seat Tightness (P12)	Air	60 seconds	No visible leaks	PASS
2	Overturn Seat Tightness	Water	60 seconds	1 drop/second	PASS

SET PRESSURE

From 100 - 300 kpa

TYPE TEST	TEST PRESSURE
Pressure (open)	220 kpa