



65mm THREADED COMBINED VACUUM/PRESSURE RELIEF VALVE

316 Stainless Steel

A.D.R. COMPLIANT & CERTIFIED

BRITISH STANDARD EN14596:2018

DATA SHEET and MATERIAL CERTIFICATE

for

PRODUCT CODE: AMF-RV-65VP-TH-V2-ADR-316

SN: ####

PART	MATERIAL
MAIN BODY	G316 STAINLESS STEEL
MOVING PARTS	G316 STAINLESS STEEL
SPRINGS	G316 STAINLESS STEEL
O-RING	VITON ENCAPSULATED

* - If applicable, copies of supplier material certificates available on request

PRODUCTION TEST REQUIREMENTS

Acceptance criteria: as per table A.5 (EN12266-1:2012)

"A" No visually detectable leaks for the duration of the test

TEST #	TEST TYPE	TEST FLUID	TEST DURATION Table A.4.	TEST CRITERIA Table A.5	RESULT
1	Seat Tightness	Water	60 seconds	No visible leaks	PASS
2	Overturn Seat Tightness	Water	60 seconds	1 drop/second	PASS

TESTING PRESSURE

TYPE TEST	TEST PRESSURE
Pressure	300 kPa
Vacuum	21 kPa