





PARTS LIST					
ITEM	QTY	PART NUMBER	MATERIAL	DESCRIPTION	MASS
1	1	MHA_4.5_DISH	316L	PL 4.5 X 562 X 562	7,964 kg
2	1	MH_RING	316L	PL 4.5 X 45 X 2000	2,080 kg
3	6	MH_LID LUG	316L	PL 4.5 X 67 X 125	0,200 kg
4	1	MH_HINGE LUG	316L	PL 4.5 X 90 X 203	0,449 kg
5	1	MH_HANDLE	316L	RB 8 X 160	0,065 kg
6	1	MHA_SEAL	Hyp	Hypalon, 496 x 15 x 15	0,335 kg
7	1	AMF-FL-124-8H-T-316L	316L	16 TH x 124mm PCD x 8 H x M10 tapped	1,136 kg
8	8	M10 spring washer	A2	10mm ID split washer	0,004 kg
9	8	M10 x 25mm hex	A2	10mm OD x 25mm full thread	0,026 kg
10	1	PTFE GASKET	PTFE	111.0 OD x 89.0 ID , 3 TH	0,010 kg
12	1	AMF_RV_80PRE_ADR_316L	316L	80mm PRESSURE RELIEF VALVE	0,000 kg

DESIGN CODE : EN14025:2018
DESIGN PRESSURE : 2 Bar
DESIGN TEMPERATURE : -20° to 50° C
MATERIAL OF CONSTRUCTION : SS 316L / 1.4404
PROCESS LIQUID AND CLASSIFICATION : CLASS 3 LIQUID
SANS 347 CLASSIFICATION : FLUID GROUP 1, CATEGORY 1
REQUIRED BOLT TORQUE : 3472 N PER BOLT

NOTE:
ALL THREADED PARTS TO BE GREASED
WITH COPPER COMPOUND

NO TRANSFER OF INTELLECTUAL PROPERTY : Any & all drawings, documentation, information or data provided by AMF to be used solely for the use intended by AMF,nor may it be shared, copied, distributed or disseminated in any manner whatsoever. All intellectual property, including AMF's drawings,shall remain the sole property of AMF.



AMF
ALLGEMEINE MASCHINEN FABRIK

APPROVED
R.P.M.J.

TITLE
**6 LUG 4.5mm MANHOLE COVER
FITTED WITH 80mm PRESSURE RELIEF VALVE
PARTS ASSEMBLY**

SIZE
A2

DWG NO
AMF_MHA_6_4.5_VE_80P_ADR_316L

REV

SCALE
1 : 1

SHEET 1 OF 1