




PARTS LIST					
ITEM	QTY	PART NUMBER	MATERIAL	DESCRIPTION	MASS
1	1	MH_6.0_DISH	316L	PL 6 x 560 x 560	10,655 kg
2	1	MH_RING	316L	PL 4.5 X 45 X 2000	2,080 kg
3	6	MH_LID LUG 6mm	316L	PL 6 X 67 X 125	0,268 kg
4	1	MH_HINGE LUG	316L	PL 4.5 X 90 X 203	0,449 kg
5	1	MH_HANDLE	316L	RB 8 X 123	0,065 kg
6	1	MHA_SEAL	HYP	Hypalon, 496 x 15 x 15	0,335 kg
7	1	AMF-FL-124-8H-T-316L	316L	16 TH x 124mm PCD x 8 H x M10 tapped	1,136 kg
10	8	M10 spring washer	A2	10mm ID split washer	0,004 kg
11	8	M10 x 25 Hex	A2	10mm OD x 25mm Full thread bolt	0,026 kg
12	1	PTFE GASKET	PTFE	111.0 OD x 89.0 ID , 3 TH	0,010 kg
13	1	AMF_RV_65VP_FL_V2_ADR_316L	316L	65mm Relief Valve	0,519 kg

NOTE:
ALL THREADED PARTS TO BE GREASED
WITH COPPER COMPOUND

DESIGN CODE : EN14025:2018
DESIGN PRESSURE : 3 Bar
DESIGN TEMPERATURE : -20° to 50° C
HYDROSTATIC TEST PRESSURE : 400 kPa
TEST FLUID : WATER
MATERIAL OF CONSTRUCTION : SS 316L / 1.4404
PROCESS LIQUID AND CLASSIFICATION : CLASS 3 LIQUID
SANS 347 CLASSIFICATION : FLUID GROUP 1, CATEGORY 1
REQUIRED BOLT TORQUE : 3472 N PER BOLT

NO TRANSFER OF INTELLECTUAL PROPERTY : Any & all drawings, documentation, information or data provided by AMF to be used solely for the use intended by AMF,nor may it be shared, copied, distributed or disseminated in any manner whatsoever. All intellectual property, including AMF's drawings,shall remain the sole property of AMF.



APPROVED
R.P.M.J.

TITLE
**6 LUG 6mm MANHOLE COVER
FITTED WITH 65mm RELIEF VALVE
PARTS ASSEMBLY**

DWG NO
AMF_MHA_6_6.0_VE_65VP_FL_ADR_316L

SCALE
1 : 1

REV

SHEET 1 OF 1